

REBAR SPIKE :: FS-2

Many of the rubber products TCT provides require some form of hardware for mounting. TCT's various fastener systems provide the correct tools for mounting and using your new TCT products. Each fastener system is designed for mounting products to a different surface, making sure you have the best option to fit your needs. All of the fastener systems are rust resistant and easy to install, so you'll quickly be able to start using your TCT products and not spend time installing. Additionally, the fastener systems are also easily removed, so that the products can be easily removed. Not sure which fastener system is best for your applications? Contact our Sales Manager for more information.



FEATURES

- Rebar Spike is perfect for use on Asphalt, Gravel, or Dirt
- Easy to use
- Meets many engineering specifications for installation
- Welded washer to form a flat surface to make contact with during installation. Prevents the spike from being driven too far in

SPECIFICATIONS

- Rebar Spike
 - Contains The Following
 - 14" long #4 (13 mm) rebar grade 60, with end cut at 45°
 - 7/16" Grade 8 Thick USS Flat Washer welded to end to for head on spike
 - Weight: 0.77 lbs

ADDITIONAL PRODUCTS

- Various fastener systems used for mounting to different surfaces (FS-1, FS-3)



We invite you to learn more about our products.

874 Old Albany Shaker Road
Latham, NY 12110
USA

<http://www.tire-conversion.com>
sales@tire-conversion.com
518.372.1300

