

SPEED BUMPS :: VR-206-11M

When designing parking lots, it is important to ensure both pedestrian and driver safety. Using bumps, humps and parking stops from TCT can increase customer safety while limiting potential damage. Speed bumps and humps ensure that drivers decrease their speed in high-traffic areas, and are easily transported to wherever they may be needed. They are made from durable molded rubber that will withstand extreme temperatures. The speed bumps and humps include a textured surface, making them safe to use in inclement weather. They can also be used in construction areas to help slow down traffic while keeping workers safe. The speed bumps are easily set up wherever you need decreased traffic speeds.



FEATURES

- Made of durable, molded rubber
- Able to withstand extreme temperatures without cracking or drying out
- Designed to be used at speeds of 0-5mph
- Four mounting holes for easy installation
- Textured surface ensures grip and traction, even in adverse conditions
- Eight reflective yellow squares and six reflective eyelets easily spotted by motorists
- Two 1 1/2" channels running underneath may also be used for cable protection

SPECIFICATIONS

- Black middle piece with eight reflective squares and six reflective eyelets
- Weight: 65lbs/29.48kg
- Height: 3"/7.62cm
- Length: 72"/182.88cm
- Width: 12"/30.48cm
- Four molded holes for mounting 6" on center from long edge. Holes are 8" from each end on center. Middle holes are 16" center to center from end holes.

ADDITIONAL PRODUCTS

- Various fastener systems used for mounting to different surfaces: FS-1, FS-2 and FS-3
- Corresponding end piece: VR-206-11E (sold separately)



We invite you to learn more about our products.

874 Old Albany Shaker Road
Latham, NY 12110
USA

<http://www.tire-conversion.com>
sales@tire-conversion.com
518.372.1300

