

## SPEED HUMP :: VR-206-10E

When designing parking lots, it is important to ensure both pedestrian and driver safety. Using bumps, humps and parking stops from TCT can increase customer safety while limiting potential damage. Speed bumps and humps ensure that drivers decrease their speed in high-traffic areas, and are easily transported to wherever they may be needed. They are made from durable molded rubber that will withstand extreme temperatures. The speed bumps and humps include a textured surface, making them safe to use in inclement weather. They can also be used in construction areas to help slow down traffic while keeping workers safe. The speed bumps are easily set up wherever you need decreased traffic speeds.



### FEATURES

- Made of durable, molded rubber
- Ideal for indoor or outdoor use
- Able to withstand extreme temperatures without cracking or drying out
- Features three mounting holes on each end piece
- Grooved surfaces ensure grip and traction, even in adverse conditions
- Easily attach middle sections together to create custom lengths

### SPECIFICATIONS

- Black rectangular end piece (male and female), sold in sets of two. Attaches to middle sections (sold separately)
- Weight: 15lbs/6.80kg
- Height: 2"/5.08cm
- Length: 35 1/4"/89.53cm
- Width: 9 3/4"/24.76cm (male ends feature two knobs that protrude an additional 3/4", used to lock into female counterpart. Female ends feature two 3/4" indentations used to accept male counterpart)

### ADDITIONAL PRODUCTS

- Various fastener systems used for mounting to different surfaces: FS-1, FS-2 and FS-3
- Corresponding middle sections: VR-206-10M (sold separately)