

SPEED BUMPS :: VR-206-8E

When designing parking lots, it is important to ensure both pedestrian and driver safety. Using bumps, humps and parking stops from TCT can increase customer safety while limiting potential damage. Speed bumps and humps ensure that drivers decrease their speed in high-traffic areas, and are easily transported to wherever they may be needed. They are made from durable molded rubber that will withstand extreme temperatures. The speed bumps and humps include a textured surface, making them safe to use in inclement weather. They can also be used in construction areas to help slow down traffic while keeping workers safe. The speed bumps are easily set up wherever you need decreased traffic speeds.



FEATURES

- Made of durable, molded rubber
- Able to withstand extreme temperatures without cracking or drying out
- Designed to be used at speeds of 10-15mph
- One mounting hole per end piece for easy installation
- Two knobs that lock into corresponding middle section for ease of installation
- Textured surface ensures grip and traction, even in adverse conditions

SPECIFICATIONS

- Black end piece with one mounting hole and two interlocking knobs, easily attaches to middle sections (sold separately)
- Weight: 4lbs/1.81kg
- Height: 2"/5.08cm
- Length: 6"/15.24cm (features two knobs that protrude an additional 2" that insert into corresponding middle section)
- Width: 12"/30.48cm
- 1 hole for mounting 6" on center from edge and 4 1/8" from end. Supports up to 5/8" lag with head 1 1/2" max

ADDITIONAL PRODUCTS

- Various fastener systems used for mounting to different surfaces: FS-1, FS-2 and FS-3
- Corresponding middle sections: VR-206-8M (sold separately)