



DESIGN.
ENGINEER.
MANUFACTURE.



VR-206-11E Speed Bumps

VR-206-11E



When designing parking lots, it is important to ensure both pedestrian and driver safety. Using bumps, humps and parking stops from TCT can increase customer safety while limiting potential damage. Speed bumps and humps ensure that drivers decrease their speed in high-traffic areas, and are easily transported to wherever they may be needed. They are made from durable molded rubber that will withstand extreme temperatures. The speed bumps and humps include a textured surface, making them safe to use in inclement weather. They can also be used in construction areas to help slow down traffic while keeping workers safe. The speed bumps are easily set up wherever you need decreased traffic speeds.

Features

Made of durable, molded rubber
Able to withstand extreme temperatures without cracking or drying out
Designed to be used at speeds of 0-5mph
One mounting hole per end piece for easy installation
Two knobs that lock into corresponding middle section for ease of installation
Textured surface ensures grip and traction, even in adverse conditions

Specifications

Black end piece with one mounting hole and two interlocking knobs, easily attaches to middle section (sold separately)	
Weight	8 lbs / 3.63 kg
Height	3" / 7.62 cm
Length	7 1/2" / 19.05 cm (features two knobs that protrude an additional 2" that insert into corresponding middle section)
Width	12" / 30.48 cm
1 hole for mounting 6" on center from edge and 6" from end. Supports up to 5/8" lag with head 1 1/2" max	

ADDITIONAL PRODUCTS

- Various fastener systems used for mounting to different surfaces: FS-1, FS-3
- Corresponding middle section: VR-206-11M (sold separately)