



VR-206-9E Speed Bumps

VR-206-9E



Features

Made from durable molded rubber
Ideal for indoor or outdoor use
Able to withstand extreme temperatures without cracking or drying out
Easily attach middle sections together to create custom lengths
Grooved surfaces ensure grip and traction, even in adverse conditions

ADDITIONAL PRODUCTS

- Various fastener systems used for mounting to different surfaces: FS-1, FS-3
- Corresponding middle sections: VR-206-9M (sold separately)

When designing parking lots, it is important to ensure both pedestrian and driver safety. Using bumps, humps and parking stops from TCT can increase customer safety while limiting potential damage. Speed bumps and humps ensure that drivers decrease their speed in high-traffic areas, and are easily transported to wherever they may be needed. They are made from durable molded rubber that will withstand extreme temperatures. The speed bumps and humps include a textured surface, making them safe to use in inclement weather. They can also be used in construction areas to help slow down traffic while keeping workers safe. The speed bumps are easily set up wherever you need decreased traffic speeds.

Specifications

_		
Black rectangular end piece (male and female), sold in sets of two. Attaches to middle sections (sold separately)		
Weight	9lbs/4.08kg	
Height	11/8"/2.86cm	
Length	24"/60.96cm	
Width	8"/20.32cm (Male ends contain 2 knobs that protrude 1/2" locking into female counterpart. Female ends contain 2 indentations measuring 1/2" that lock into male counterparts)	
Two molded holes for mounting located 2 1/8" from short edges and 3 1/8" for inside edge		

