



VR-206-9M Speed Bumps

VR-206-9M



Features

Made from durable molded rubber
Ideal for indoor or outdoor use
Able to withstand extreme temperatures without cracking or drying out
Easily attach middle sections together to create custom lengths
Grooved surfaces ensure grip and traction, even in adverse conditions
8 reflective yellow squares easily spotted by motorists

ADDITIONAL PRODUCTS

- Various fastener systems used for mounting to different surfaces: FS-1, FS-3
- Corresponding end pieces: VR-206-9E (sold separately and in pairs)

When designing parking lots, it is important to ensure both pedestrian and driver safety. Using bumps, humps and parking stops from TCT can increase customer safety while limiting potential damage. Speed bumps and humps ensure that drivers decrease their speed in high-traffic areas, and are easily transported to wherever they may be needed. They are made from durable molded rubber that will withstand extreme temperatures. The speed bumps and humps include a textured surface, making them safe to use in inclement weather. They can also be used in construction areas to help slow down traffic while keeping workers safe. The speed bumps are easily set up wherever you need decreased traffic speeds.

Specifications

	•	
	Black rectangular speed hump with eight reflective squares, grooved surface to help with traction. Features four mounting holes	
	Weight	20 lbs / 9.07 kg
	Height	11/8" / 2.86 cm
	Length	24" / 60.96 cm
	Width	18 3/4" / 47.63 cm (Two knobs protrude 1/2" extra on one side and two indentations 1/2" on the female side)
		ounting holes located 1 3/8" from long and 2" from short edge

