

DESIGN. ENGINEER. MANUFACTURE.



WCR-9 Wheel Chocks

WCR-9



Features

Made from recycled tire rubber


Able to withstand extreme temperatures without cracking or drying out

Designed for downward pressure to help lock wheel chock into place

Eye hooks on each chock can be used to rope two units together, move units with ease, or hang units when not in use

ADDITIONAL PRODUCTS

- Replacement Eye-hook
- Custom length rope available in different styles
- Smooth wheel chock: WCR-9Y
- One-sided ribbed wheel chock: WCR-7/WCR-7Y
- Two-sided ribbed wheel chock: WCR-5/WCR-5Y
- Military wheel chock: MWC14/MWC-20
- Small machinery wheel chock: SWC-7/SWC-7Y



Specifications

Standard smooth, two-sided pyramid wheel chock with eye-hook	
Weight	10 lbs / 4.54 cm
Height	5″ / 12.7 cm
Length	10" / 25.4 cm
Width	7 3/4" / 19.68 cm

www.tire-conversion.com

TCT US Latham, New York, USA

(518) 372-1300 sales@tire-conversion.com TCT Europe Fife, Scotland, UK

+44 (0)131 524 8183 sales-europe@tire-conversion.com TCT Europe Christchurch, Dorset, UK

+44 (0)131 524 8183 sales-europe@tire-conversion.com